



- EXTREMELY LINEAR EXCURSION DESIGN
- PPM CONE WITH TWIN ROLL SHAPE RUBBER SURROUND
- DIE CAST BASKET, PPM PHASE PLUG
- INTENDED FOR BASS REFLEX ENCLOSURES
- VENTED POLE PIECE
- CCAW WITH KAPTON BOBBIN/CONEX SPIDER

6.5" PPM WOOFER



DIAPHRAGM MTL	PPM
SURROUND MTL	Rubber
NOMINAL IMPEDANCE	8 W
DCR IMPEDANCE	6 W
SENSITIVITY 1W/1m	89 dB
FREQUENCY RESPONSE	45-10K Hz
FREE AIR RESONANCE	45 Hz
VOICE COIL DIAMETER	25 mm
AIR GAP HEIGHT	6 mm
RATED POWER INPUT	30 W
MAXIMUM POWER INPUT	60 W
FORCE FACTOR, BL	6.5 TM
MAGNET WEIGHT (16oz)	451 g
MOVING MASS	10.55 g
FERRO FLUID ENHANCED	No
SUSPENSION COMPL.	979MN <sup>-1</sup>
EFFEC.PISTON AREA	0.014M <sup>2</sup>
Levc	0.49mH
Zo	43.55ohm
X-max	4 mm
Vas	27.3 Litr.
Qts	0.43
Qms	3.09
Qes	0.49



**CLOSE**