



- LONG THROW HIGH POWER LOADING DESIGN
- OVAL SHAPE PAPER CONE WITH TWIN ROLL RUBBER SURROUND
- NEODYMIUM MOTOR DESIGN, VENTED POLE PIECE
- STAMPED STEEL BASKET, MAGNETIC SHIELDED
- SUITABLE FOR MID BASS APPLICATION
- VERY SMOOTH FREQUENCY RESPONSE

## 6\*9" MID BASS



DIAPHRAGM MTL	Paper
SURROUND MTL	Rubber W Shape
NOMINAL IMPEDANCE	8 W
DCR IMPEDANCE	6.5 W
SENSITIVITY 1W/1m	89 dB
FREQUENCY RESPONSE	40-5.5k Hz
FREE AIR RESONANCE	40 Hz
VOICE COIL DIAMETER	38.5 mm
AIR GAP HEIGHT	14 mm
RATED POWER INPUT	60 W
MAXIMUM POWER INPUT	120 W
FORCE FACTOR, BL	8.3 TM
MAGNET WEIGHT (oz)	Neodymium
MOVING MASS	23 g
FERRO FLUID ENHANCED	No
SUSPENSION COMPL.	684.522 MN <sup>-1</sup>
EFFEC.PISTON AREA	0.0226 M <sup>2</sup>
Levc	0.81 mH
Zo	33.7 ohm
X-max	4.5 mm
Vas	49.6 Litr.
Qts	0.44
Qms	2.28
Qes	0.55



**CLOSE**